

MIRANDA HOUSE
UNIVERSITY OF DELHI

Date: 07.02.2022

Notice Inviting Quotation

Sealed quotation an invited from the civil working contractors of the College/ CPWD/ Delhi University.
"Repair and Renovation of Server room"

Publishing Date	08/02/2022 at 1:00 P.M.
Estimated Cost	85136.74/-
Quotation Fee	200/- In favour of Principal, Miranda House University of Delhi.
Completion Time	30 Days
Quotation Submission Date	16/02/2022 at 4.00pm
Quotation Opening Time	17/02/2022 at 3.00pm

- Bids will be opened as per date/time on mentioned above.
- Bidder has down loaded the Quotation from the college website.
- The above Quotation should reach Miranda House College Office by hand on or before 16/02/2022 up to 4:00 p.m.
- The tender fee is non- Replaceable.
- The unit rate for any items should be Quotation inclusive of GST.
- For general rules and directive condition of Contract, the tender shall refer to "CPWD General Condition of Contract – 2014". Except for exception mentioned in this document, which will form a part of the Agreement will up to date correction slips.

B de

Offg. Principal

Jyoti Prakash
07/02/2022

MIRANDA HOUSE					
UNIVERSITY OF DELHI					
ESTIMATE					
Repair and Renovation of Server room.					
S.NO	ITEMS	QTY	UNIT	RATE	AMOUNT
1	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer- n-Charge. 14.1.1 With cement mortar 1:4 (1 cement : 4 fine sand) sqm 417.80	15	SQM		
2	Fixing chowkhats in existing opening including embedding chowkhats in floors or walls cutting masonry for holdfasts, embedding hold fasts in cement concrete blocks of size 15 x 10 x 10 cm with cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size), painting two coats of approved wood preservative to sides of chowkhats and making good the damages to walls and floors as required complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge. 14.2.1 Door chowkhats each 1366.85	2	NOS		
3	Renewing glass panes and refixing existing wooden fillets: 14.7.2 Float glass panes of nominal thickness 5 mm (weight not less than 12.5kg/sqm) sqm 1284.20	2	SQM		
4	Providing and fixing 25 mm thick shutters for cup board etc. : 14.26.1 Panelled or panelled & glazed shutters : 14.26.1.1 Superior class teak wood including nickel plated bright finished M.S. piano hinges with necessary screws. sqm 4456.60	3	SQM		

5	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. sqm 1030.30	28	SQM		
6	Providing wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position with hold fast lugs or with dash fasteners of required dia & length (hold fast lugs or dash fastener shall be paid for separately). 9.1.2 Sal wood cum 105327.20	0.2	CUM		
7	Distemping with oil bound washable distemper of approved brand and manufacture to give an even shade : 13.41.1 New work (two or more coats) over and including water thinnable priming coat with cement primer sqm 153.45	25	SQM		
8	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : 13.61.1 Two or more coats on new work sqm 121.55	15	SQM		
9	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead. sqm 39.00	30	SQM		
10	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. sqm 115.15	30	SQM		
				TOTAL	